



## T-500

Shimano Cues 20-speed / Disc

| Article   | Inch | Frame size    | Color      |
|-----------|------|---------------|------------|
| 102420131 | 28"  | Gents, 52 cm  | ebony matt |
| 102420132 | 28"  | Gents, 57 cm  | ebony matt |
| 102420133 | 28"  | Gents, 62 cm  | ebony matt |
| 102420134 | 28"  | Gents, 67 cm  | ebony matt |
| 102420135 | 28"  | Ladies, 45 cm | ebony matt |
| 102420136 | 28"  | Ladies, 50 cm | ebony matt |
| 102420137 | 28"  | Ladies, 55 cm | ebony matt |
| 102420138 | 28"  | Ladies, 60 cm | ebony matt |

Technical changes and changes in equipment reserved, color deviations possible.

|                         |                         |                                                                                                                |
|-------------------------|-------------------------|----------------------------------------------------------------------------------------------------------------|
| General                 | <b>Frame</b>            | 25 CrMo 4, double butted                                                                                       |
|                         | <b>Head set</b>         | Ritchey Comp Logic V2                                                                                          |
|                         | <b>Fork</b>             | 28" aluminum                                                                                                   |
|                         | <b>Shifting System</b>  | Shimano Cues RD-U6020, 10-speed                                                                                |
|                         | <b>Derailleur</b>       | Shimano Cues FD-U6010, 2-speed                                                                                 |
|                         | <b>Brakes</b>           | Shimano Deore BR-MT410 (front 160 mm / rear 160 mm)                                                            |
|                         | <b>Headlight</b>        | Busch & Müller Lumotec Eyc, 50 LUX                                                                             |
|                         | <b>Rear light</b>       | Busch & Müller, Toplight 2C                                                                                    |
|                         | <b>Carrier</b>          | vsf fahrradmanufaktur Basic Tour 2.0, strutless, with spring flap, compatible with Racktime Snap-It 2.0 System |
|                         | <b>Saddle</b>           | Selle Royal Essenza                                                                                            |
|                         | <b>Seat post</b>        | Levelnine, patent, aluminum, 27.2 mm, 300 mm                                                                   |
|                         | <b>Pedals</b>           | Marwi SP-823, black                                                                                            |
|                         | <b>Kickstand</b>        | Zoom, rear kickstand                                                                                           |
| Cockpit                 | <b>Chainguard</b>       | Shimano chain guard                                                                                            |
|                         | <b>Mudguard</b>         | SKS A56, plastic                                                                                               |
|                         | <b>Other</b>            | max load 140 kg                                                                                                |
|                         | <b>Weight</b>           | 14.1 kg                                                                                                        |
| Wheels/Tires/Drivetrain | <b>Stem</b>             | Levelnine, aluminum, a-head, 31.8 mm                                                                           |
|                         | <b>Handlebars</b>       | Levelnine, Trekking, aluminum, 640 mm                                                                          |
|                         | <b>Grips</b>            | Herrmans Grit D33, with clamp                                                                                  |
|                         | <b>Shift lever</b>      | Shimano Cues SL-U6000, 2-/10-speed, with display                                                               |
|                         | <b>Brake lever</b>      | Shimano Deore BL-MT402, 3-finger brake lever                                                                   |
|                         | <b>Tires</b>            | Schwalbe Marathon, 40-622, reflex                                                                              |
| Wheels/Tires/Drivetrain | <b>Rims</b>             | Schürmann YAK19 Disc Double Wall Alloy Rim, 36 holes                                                           |
|                         | <b>Spokes</b>           | Niro 2,0 mm                                                                                                    |
|                         | <b>Front Hub</b>        | Shutter Precision PL-8, hub dynamo, Centerlock, 36 holes                                                       |
|                         | <b>Rear Hub</b>         | Shimano Deore FH-M6000, Centerlock, 36 holes                                                                   |
|                         | <b>Sprocket</b>         | Shimano Cues CS-LG300, 10-speed, 11-39 teeth                                                                   |
|                         | <b>Chain</b>            | Shimano CN-LG500                                                                                               |
|                         | <b>Inner bearing</b>    | Shimano BB-MT501B, for Hollowtech II, BSA                                                                      |
|                         | <b>Bottom bracket</b>   | Shimano Cues FC-U6000-2, 170 mm, Hollowtech II, 46/30 teeth                                                    |
|                         | <b>Gear ratio (f:r)</b> | 46/30 teeth : 11-39 teeth                                                                                      |