



T-100

Shimano Cues 18-speed / HS11

Article	Inch	Frame size	Color
102420261	28"	Gents, 52 cm	ebony matt
102420262	28"	Gents, 57 cm	ebony matt
102420263	28"	Gents, 62 cm	ebony matt
102420265	28"	Ladies, 45 cm	ebony matt
102420266	28"	Ladies, 50 cm	ebony matt
102420267	28"	Anglais, 55 cm	ebony matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CroMo 4
	Head set	Ritchey Comp Logic V2
	Fork	28" CroMo 4
	Shifting System	Shimano Cues RD-U3020, 9-speed
	Derailleur	Shimano Cues FD-U4010, 2-speed
	Brakes	Magura HS11, including Brakebooster
	Headlight	Busch & Müller Lumotec Dopp N plus, 35 LUX
	Rear light	Busch & Müller, Toplight 2C
	Carrier	vsf fahrradmanufaktur Basic Tour 2.0, strutless, with spring flap, compatible with Racktime Snap-It 2.0 System
	Saddle	Selle Royal Rio
	Seat post	Humpert Ergotec Atar, patent, aluminum, 27.2 mm, 300 mm
	Pedals	Marwi SP-811
	Kickstand	Zoom, rear kickstand
	Chainguard	Shimano chain guard
Cockpit	Mudguard	SKS A53, plastic
	Other	max load 140 kg
	Weight	15.4 kg
	Stem	Humpert Ergotec Octopus, 31,8 mm, angle adjustable, safety level 4
	Handlebars	Humpert Ergotec MAS Trekking, 660 mm, safety level 4
	Grips	Herrmans DD37, with clamp
	Shift lever	Shimano Cues SL-U4000, 2-/9-speed
	Brake lever	Magura HS11
Wheels/Tires/Drivetrain	Tires	Schwalbe Marathon Citizen, 47-622, reflex
	Rims	Schürmann YAK19 Double Wall Alloy Rim, 36 holes
	Spokes	Niro 2,0 mm
	Front Hub	Shimano DH-3000, hub dynamo, 36 holes
	Rear Hub	Shimano FH-TX500, 36 holes
	Sprocket	Shimano Cues CS-LG300, 9-speed, 11-36 teeth
	Chain	Shimano CN-LG500
	Inner bearing	Shimano BB-MT501B, for Hollowtech II, BSA
	Bottom bracket	Shimano Cues FC-U4010-2, 170 mm, Hollowtech II, 46/30 teeth
	Gear ratio (f:r)	46/30 teeth : 11-36 teeth