



TX-400

Shimano Cues 22-speed / HS33

Article	Inch	Frame size	Color
102420031	26"	Gents, 47 cm	black olive matt
102420032	26"	Gents, 52 cm	black olive matt
102420033	26"	Gents, 57 cm	black olive matt
102420035	26"	Ladies, 45 cm	black olive matt
102420036	26"	Ladies, 50 cm	black olive matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted
	Head set	Ritchey Comp Logic V2
	Fork	26" 25CrMo 4
	Shifting System	Shimano Cues RD-U6020-11, 11-speed
	Derailleur	Shimano Cues FD-U8010, 2-speed
	Brakes	Magura HS33, including Brakebooster
	Headlight	Busch & Müller Lumotec IQ-XS, 70 LUX
	Rear light	Busch & Müller, Toplight Mini Plus
	Carrier	Tubus Cargo / Tubus Tara Lowirder
	Saddle	Selle Royal Scientia
	Seat post	Humpert Ergotec Skalar, patent, aluminum, 27.2 mm, 400 mm, safety level 6
	Pedals	VP-196 aluminum
	Kickstand	0611, rear kickstand
	Chainguard	Shimano chain guard
Cockpit	Mudguard	SKS A60, plastic
	Other	max load 140 kg
	Weight	15.9 kg
	Stem	Humpert Ergotec Piranha 2, 31,8 mm, safety level 6
	Handlebars	Humpert Ergotec Trekking, aluminum, 620 mm, safety level 6
	Grips	Ergon GP3, with clamp and integrated Barends
Wheels/Tires/Drivetrain	Shift lever	Shimano Cues SL-U8000, 2-/11-speed, with gear indicator
	Brake lever	Magura HS33
	Tires	Schwalbe Marathon Mondial, 50-559, reflex
	Rims	Schürmann YAK19 Double Wall Alloy Rim, 36 holes
	Spokes	Niro ED 2,34 mm
	Front Hub	Shutter Precision PV-8, hub dynamo, 36 holes
	Rear Hub	Shimano FH-QC400-HM, 36 holes
	Sprocket	Shimano Cues CS-LG400, 11-speed, 11-45 teeth
	Chain	Shimano CN-LG500
	Inner bearing	Shimano BB-MT501B
	Bottom bracket	Shimano Cues FC-U6010-2, 170 mm, Hollowtec II, 46/32 teeth
	Gear ratio (f:r)	46/32 teeth : 11-45 teeth