



TX-800

Shimano Cues 22-speed / Disc

Article	Inch	Frame size	Color
102420011	28"	Gents, 52 cm	slate matt
102420012	28"	Gents, 57 cm	slate matt
102420013	28"	Gents, 62 cm	slate matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	25 CrMo 4, double butted
	Head set	Ritchey Comp Logic V2
	Fork	28" 25CrMo 4, thru-axle 12 x 100 mm
	Shifting System	Shimano Cues RD-U8020, 11-speed
	Derailleur	Shimano Cues FD-U8010, 2-speed
	Brakes	Shimano Deore XT BR-M8100 (front 180 mm / rear 160 mm)
	Headlight	Busch & Müller Lumotec IQ-XS, 70 LUX
	Rear light	Busch & Müller, Line LED
	Carrier	Tubus Logo Evo / Tubus Tara Lowrider
	Saddle	Selle Royal Scientia
	Seat post	Humpert Ergotec Skalar, patent, aluminum, 27.2 mm, 400 mm, safety level 6
	Pedals	VP-196 aluminum
	Kickstand	Comp, rear kickstand
	Chainguard	Shimano chain guard
Cockpit	Mudguard	SKS A56, plastic
	Other	max load 140 kg
	Weight	16.5 kg
	Stem	Humpert Ergotec Piranha 2, 31,8 mm, safety level 6
	Handlebars	Humpert Ergotec Trekking, aluminum, 620 mm, safety level 6
	Grips	Ergon GP3, with clamp and integrated Barends
Wheels/Tires/Drivetrain	Shift lever	Shimano Cues SL-U8000, 2-/11-speed, with display
	Brake lever	Shimano Deore XT BL-T8100, 3-finger brake lever
	Tires	Schwalbe Marathon Mondial, 47-622, reflex
	Rims	Schürmann YAK19 Disc Double Wall Alloy Rim, 36 holes
	Spokes	Niro ED 2,34 mm
	Front Hub	Shutter Precision PL-7, 12 x 100 mm, hub dynamo, Centerlock, 36 holes
	Rear Hub	Shimano XT FH-UR600, Centerlock, 36 holes
	Sprocket	Shimano Cues CS-LG400, 11-speed, 11-45 teeth
	Chain	Shimano CN-LG500
	Inner bearing	Shimano BB-MT501B, for Hollowtech II, BSA
	Bottom bracket	Shimano Cues FC-U8000-2, 170 mm, Hollowtech II, 46/32 teeth
	Gear ratio (f:r)	46/32 teeth : 11-45 teeth